



## Features & Benefits

Hospital Grade GFCI self-test

## Specifications

## General Info

Product LinePass & SeymourReplaced by Part NumberPT2097H6NTLTRLAColorLight AlmondCountry Of OriginChinaApplication SectorResidential/CommercialStandardcULus, UL Listed, FSULListing Agencies / 3rd Part XgenciesVesVescULus ListedYesVesVesIs Tamper-ResistantYesInterrupt Rating4AFrequency Rating60 HzTrip Range5±1 mAConnectionBack and Side WireAmperage20 A					
Application Sector     Residential/Commercial     Standard     cULus, UL Listed, FSUL       Listing Agencies / 3rd Party Agencies     CULus Listed     Yes       cULus Listed     Yes     Interrupt Rating     4 A       Is Tamper-Resistant     Yes     Interrupt Rating     5±1 mA	Product Line	Pass & Seymour	Replaced by Part Number	PT2097HGNTLTRLA	
Listing Agencies / 3rd Party Agencies cULus Listed Yes Technical Information Is Tamper-Resistant Yes Interrupt Rating 4 A Frequency Rating 60 Hz Trip Range 5±1 mA	Color	Light Almond	Country Of Origin	China	
cULus ListedYesTechnical InformationYesIs Tamper-ResistantYesFrequency Rating60 HzTrip Range5±1 mA	Application Sector	Residential/Commercial	Standard	cULus, UL Listed, FSUL	
Technical Information         Is Tamper-Resistant       Yes         Interrupt Rating       4 A         Frequency Rating       60 Hz         Trip Range       5±1 mA	Listing Agencies / 3rd Party Agencies				
Is Tamper-Resistant     Yes     Interrupt Rating     4 A       Frequency Rating     60 Hz     Trip Range     5±1 mA	cULus Listed	Yes			
Frequency Rating 60 Hz Trip Range 5±1 mA	Technical Information				
	ls Tamper-Resistant	Yes	Interrupt Rating	4 A	
Connection Back and Side Wire Amperage 20 A	Frequency Rating	60 Hz	Trip Range	5±1 mA	
	Connection	Back and Side Wire	Amperage	20 A	

Voltage

125.0 V

Double Pole

95% Humidity, UL 94 V2

Number of Poles

Environmental Conditions