

Pass and Seymour

Hospital Grade 20A Tamper-Resistant Duplex Self-Test GFCI Receptacles with SafeLock® Protection, NAFTA-Compliant, Red

Part No. 2097HGTRNARED



Conducts an automatic test every three seconds, ensuring it's always ready to protect. If the device fails the test, the indicator light flashes to signal that the GFCI should be replaced. It also has our proven SafeLock™ Protection feature: if critical components are damaged and protection is lost, power to the receptacle is disconnected.

For more detailed information, visit our **GFCI Outlets and Receptacles** page.

Features & Benefits

Protects children: patented shutter system helps prevent improper insertion of foreign objects.

Meets NEC® Tamper-Resistant requirements.

Conducts an automatic test every three seconds, ensuring it's always ready to protect. If the device fails the test, the indicator light High-impact-resistant flashes to signal that the GFCI should be replaced. It also has our proven SafeLock™ Protection feature: if critical components are thermoplastic construction damaged and protection is lost, power to the receptacle is disconnected with tri-drive terminal screws.

Specifications

| General Info | | | |
|---------------------------------------|------------------------|--------------------------|------------------------|
| Product Line | Pass & Seymour | Color | Red |
| Country Of Origin | Mexico | Application Sector | Residential/Commercial |
| Standard | cULus, UL Listed, FSUL | | |
| Dimensions | | | |
| Product Width US | 1.72 in | Product Depth US | 0.98 in |
| Product Height US | 4.2 in | | |
| Listing Agencies / 3rd Party Agencies | | | |
| cULus Listed | Yes | | |
| Technical Information | | | |
| Interrupt Rating | 4 A | Frequency Rating | 60 Hz |
| Trip Range | 5±1 mA | Connection | Back and Side Wire |
| Amperage | 20 A | Number of Poles | Double Pole |
| Voltage | 125.0 V | Environmental Conditions | 95% Humidity, UL 94 V2 |