

Pass and Seymour 15A 125V Heavy Duty Spec-Grade Single Receptacle, Side Wire, Ivory Part No. 5251I



Heavy-Duty Spec Grade Single Receptacle Side, Wire 15A 125V

Features & Benefits

Auto-ground clip assures positive ground.

Strap tabs wrap around and lock down on face to prevent strap from separating from face and back body.

Heavy-duty, corrosion-resistant zinc-plated steel strap for added strength.

Backed-out tr-drive steel terminal screws. Internal screw-pressure-plate back and side wire capability. Two back wire holes for increased wiring flexibility.

One-piece brass triple-wire power contacts for lasting retention.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C

without impact

Specifications

General Info

Product Line	Pass & Seymour	Color	lvory	
Finish	Matte	Country Of Origin	Mexico	
Number of Receptacles	1	Outlet Type	Commercial, Indoor	
Application Sector	Residential/Commercial	Standard	UL 498	
Warranty Type	1-Year Limited Warranty	Туре	Outlet	

Ш	۱ (m	ρ	n	\subseteq	ı	\cap	n	ς

Product Width US	1.38 in	Product Depth US	1.08 in			
Listing Agencies / 3rd Party Agencies						
cULus ListingNumber	140596	cULus Listed	Yes			
Technical Information						
Amperage	15 A	Number of Poles	Double Pole			
Wire Size	4 AWG	Indoor/Outdoor	Indoor			
Voltage	125.0 V					