



Wiremold
Discontinued - 6CT Evolution™ Poke Thru Surface Style Cover, Aluminum
Part No. 6CTC2AL

Surface style die-cast aluminum cover assembly in painted aluminum finish. 6CTC2 Series cover assemblies designed for use with 6STC, 6STCP and 6STCPAV Poke-Thru Stem Assemblies. NOTE: Add suffix inchTRinch to the end of the part number to indicate tamper-resistant cover assembly.



Features & Benefits

Die-cast aluminum cover assemblies: The new Evolution Series poke-thru design includes all metal die-cast aluminum cover assemblies, with two unique spring-loaded slide egress doors. No clumsy flip lids to get broken or cause an added trip hazard.

Unique cover design: The cover opens a full 180 degrees with two unique spring-loaded slide egress doors to keep wires, connections and people safe.

Surface style cover assemblies: A surface style cover is for mounting on top of the finished floor surface. The surface cover is designed to be used for carpet, tile, wood, polished concrete, or terrazzo.

Multiple finishes: Evolution Series Poke-Thru Devices are available in multiple finishes, (BK) black, (GY) gray, (NK) nickel, (BS) brass, (BZ) bronze, (AL) aluminum, (AA) brushed aluminum, (SB) satin brass, and (SN) satin nickel to seamlessly match your environment.

Specifications

General Info

Product Line	Wiremold	Replaced by Part Number	6CTC2AA, 6CTC2AA
Color	Aluminum	UPC Number	786564088288
Country Of Origin	India	Application Sector	Commercial
Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] & 314 of NEC	Type	Cover

Dimensions

Product Width US	7.25 in	Product Weight US	2.03 lb
------------------	---------	-------------------	---------

Product Volume US 60.97 cu in

Product Depth US 1.16 in

Product Height US 7.25 in

Core Hole Size 6 in

Listing Agencies / 3rd Party Agencies

cULus ListingNumber E2961

cULus Listed Yes

Additional Information

RoHS Conformant Yes

Technical Information

Number of Outlets 0
