

Pass and Seymour Flexcor® Support Grips Standard Duty, Closed Mesh, Offset Eye Grips, Cable Diameter 0.75 - 0.99 in. Part No. FC075OF



FC0750F: Standard Duty, Closed Mesh, Offset Eye Grips, Cable Diameter 0.75 - 0.99 inches, Bale Length 4-in, Mesh Length 14-in, Break Strength 960 lbs.

Features & Benefits

| Closed mesh support grips are used when the end cable is accessible. | ^{of the} Standard duty closed mesh support grips are designed for loads up to 600 lbs. |
|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Vertical runs of no more than 100 ft. | They are available in a variety of eye styles and cable ranges for supporting electrical and fiber optic cable, metal rods, and tubing. |
| Support grips are woven of corrosion-resistant tinn stainless steel wire. | ed- Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information. |
| Bale Length: 4: Mesh Length: 14 | |

Specifications

General Info

| Product Line | Pass & Seymour | Country Of Origin | Mexico | | |
|---------------------------------------|-----------------------------------------------------------|---------------------|-----------------------------------------------------|--|--|
| Construction | Support and Strain Relief Grips, Various Types of Pulling | Application Sector | Industrial | | |
| Standard | UL/CSA Approval (consult factory) | | | | |
| Dimensions | | | | | |
| Product Width US | 0.99 in | Product Length US | 13.0 in | | |
| Listing Agencies / 3rd Party Agencies | | | | | |
| CSA Listed | Yes | CSA File Number | 67507 | | |
| Technical Information | | | | | |
| Maximum Cable Range | 0.75 in | Minimum Cable Range | 0.99 in | | |
| Capacity | Various Cable Diameter Ranges | Mounting | Consult the Factory for Mounting Recommendations | | |
| Load | Approx. Break Strength: 960 | | | | |
| | | | | | |