



FC22: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.22 - 0.32 inches, Bale Length 9-in, Mesh Length 3.5-in, Break Strength 1100 lbs.

Features & Benefits

Bus drop grips are used as cable support. They relieve any direct tension from the critical connection and absorb vibration and flexing.

Bus drop grips are woven of galvanized steel wire.

They are offered with either the single eye or locking bale attachment.

Support grips are woven of corrosion-resistant tinned-stainless steel wire.

Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information.

Bale Length: 9: Mesh Length: 3.5

Specifications

General Info

Product Line	Pass & Seymour	Country Of Origin	Mexico
Construction	Various Types of Pulling, Support and Strain Relief Grips	Application Sector	Industrial
Standard	UL/CSA Approval (consult factory)		

Dimensions

Product Width US	0.32 in	Product Length US	3.5 in
------------------	---------	-------------------	--------

Listing Agencies / 3rd Party Agencies

CSA Listed	Yes	CSA File Number	67507
------------	-----	-----------------	-------

Technical Information

Maximum Cable Range	0.22 in	Minimum Cable Range	0.32 in
Capacity	Various Cable Diameter Ranges	Mounting	Consult the Factory for Mounting Recommendations
Load	Approx. Break Strength: 1100		