

Turnlok® Single Receptacle 3-Wire 15A 277V Isolated Ground



Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

IG symbol and Isolated Ground markings for easy identification and circuit delineation.

One-piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Side and external screw-pressure-plate back wire capability. Accepts #14-#10 AWG.

Specifications

General Info

Product Line	Pass & Seymour	Color	Orange
Finish	Matte	Country Of Origin	Mexico
Receptacle Type	Locking	Number of Receptacles	1
Application Sector	Industrial	Standard	UL Listed
Type	Isolated Ground		

Dimensions

Product Width US	1.437 in	Product Depth US	4.03 in
Product Height US	1.203 in		

Listing Agencies / 3rd Party Agencies

CSA Listed	Yes	cULus Listed	Yes
------------	-----	--------------	-----

CSA File Number	16063		
-----------------	-------	--	--

Technical Information

Phase	3	Number of Wires	3
-------	---	-----------------	---

Amperage	15 A	Number of Poles	Double Pole
----------	------	-----------------	-------------

NEMA Configuration Code	L7-15	Voltage	277.0 V
-------------------------	-------	---------	---------
