Wattstopper

**Digital PIR Corner Mount Sensor, 1-sided aisle, USA**

Part No. LMPX-100-4-U

The LMPX-100 Digital PIR Corner Mount Occupancy Sensor uses passive infrared (PIR) technology and one of four lenses to detect occupancy in different types of spaces for energyefficient control of lighting and plug loads. It is a digital sensor, and is part of a Wattstopper Digital Lighting Management (DLM) system.

## Features & Benefits

- Passive infrared sensor with a choice of four coverage patterns
- Quick access to Push n' Learn for system personalization
- IR transceiver for wireless configuration and remote control
- High density, long range and aisle lenses
- Component of Digital Lighting Management integrated control system
- Digital sensor with LCD display and programming pushbuttons behind snap-down cover
- Compact 2.4"" x 3"" sensor mounts easily on a wall or ceiling

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | Wattstopper | Color | White |
| UPC Number | 754182927593 | Country Of Origin | United States |
| Product Series | LMPX-100 | Features | Adjustable Time Delay, Indicator Lights, Room Controller Required, Sensitivity Adjustment |
| Installation Location | Ceiling, Wall | Included | RJ-45 Coupler |
| Standard | UL, cUL, FCC part 15, RoHS, PEP, BAA, TAA | Warranty Type | 5-Year |
| Type | Sensor | | |

## Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 2.5 in | Product Weight US | 0.3 lb |
| Product Volume US | 117.0 cu in | Product Depth US | 3.8 in |
| Product Height US | 3.0 in | | |

## Additional Information

| | |
|---|---|
| Product Environmental Profile | Yes |

## Technical Information

| | | | |
|---|---|---|---|
| Operating Temperature Min | 32 °F | Has Battery | No |
| Number of Connections | 1 | Sensor Type | Occupancy |
| Operating Temperature Max | 131 °F | Sensor Mounting Height | 10 ft |
| Sensor Technology | Passive Infrared (PIR) | Topology | Free Topology |
| Input Voltage | 24 VDC | Indoor/Outdoor | Indoor |
| Mounting Type | Ceiling Tile, J-Box, Surface | On Function | Auto On |
| Current Draw | 7 mA | Operating Temperature | 32°-131°F (0°-55°C) |
| Operating Humidity | 5-95% RH (Non-Condensing) | Sensing Range | 6 x 50 ft |
| Wire Connection Type | RJ-45 | Storage Temperature | 23° - 176° F, -5° - 80° C |