

Pass and Seymour 20A, 125V Extra-Hard Use Spec-Grade Connector, Black and White Part No. PS5369X

Straight Blade Connector 2-Pole 3-Wire 20A 125A



Features & Benefits

Unit arrives completely ready-to-wire, cuts installation time significantly.

Nylon housing provides impact and chemical resistance. Rugged two-piece cord grip provides more uniform cord retention. Internal dust shield keeps terminals free of contaminants.

Tri-drive assembly screws are standard on all All 3-wire terminals located on the same plane, allows for quick wire termination from any Specification Grade plugs and connectors. angle.

Heavy-duty brass alloy blades and contacts, resist heat rise, provide excellent conductivity.

Cord-grip screws recessed to protect installer against screwdriver head slippage.

For covering patents, see www.legrand.us/patents.

Specifications

General Info

| Pass & Seymour | Color | Black | |
|----------------|---|--|--|
| Mexico | Standard | UL 498 | |
| Straight Blade | | | |
| | | | |
| 1.516 in | Product Length US | 2.638 in | |
| encies | | | |
| Yes | | | |
| | | | |
| Yes | | | |
| | | | |
| | Mexico Straight Blade 1.516 in encies Yes | Mexico Standard Straight Blade 1.516 in Product Length US encies Yes | Mexico Standard UL 498 Straight Blade - - 1.516 in Product Length US 2.638 in encies - - Yes - - |

| Connection | Wire Grounding | Number of Wires | 3 |
|------------|----------------|-----------------|-------------|
| Amperage | 20 A | Number of Poles | Double Pole |
| Wire Size | 4 | Voltage | 125.0 V |