## **L** legrand<sup>®</sup>

Pass and Seymour Discontinued - Heavy Duty Hospital Grade Smooth Face Receptacles, Back and Side Wire, 15A, 125V, Brown Part No. PS8200HS



Heavy-Duty Hospital Grade Smooth Face Duplex Receptacle Back & Side Wire 15amp 125volt Brown

## Features & Benefits

Heavy-duty, brass strap for added strength and ground conductivity.	.032 inch thick, brass, triple-wipe power contacts for lasting retention.
Strap tabs wrap around face to prevent strap from separating from face and back body.	Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
Two drive screws anchor strap to back body and face.	Tri-drive brass terminal screws.
Internal screw-presure-plate back and side wire capability.	Two back wire holes for more wiring flexibility.
Auto-ground clip assures positive ground.	Smooth face version features an impact-resistant nylon face for ease of cleaning and less dirt build-up.
For covering patents, see www.legrand.us/patents.	For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.
Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles	

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

## Specifications

General Info						
Product Line	Pass & Seymour	Color	Brown			
Country Of Origin	United States	Application Sector	Commercial			
Standard	UL498, CSA C22.2 No. 42					
Dimensions						
Product Width US	1.322 in	Product Depth US	1.18 in			
Product Height US	2.635 in					
Listing Agencies / 3rd Party Agencies						
cULus Listed	Yes					

## **Technical Information**

Dielectric Strength	Withstands 2000V minimum	Connection	Back and side wire
Number of Wires	3	Temperature Rating	-40° - 60° C
Amperage	15 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Voltage	125.0 V
Environmental Conditions	Flammability: UL94 V2		