

Wiremold Plugmold 3 ft. Self Test GFCI 5-Outlet Power Strip, Stainless Steel Part No. S20GB306TRGFI6



The Wiremold 2000 Series raceway offers a selection of steel, aluminum, and nonmetallic raceways that provide a versatile solution for many applications. Plugmold sections offer single or alternating circuits, in standard or isolated ground receptacles. The ScuffCoat finish is scratch resistant and protects against nicks and chips while preventing color from fading.

Features & Benefits

Built-in GFCI protection. Provides GFCI protection for all outlets on Tamper-resistant receptacles. Patented shutter system the Plugmold strip and all devices plugged into them. Great for residential kitchens with multiple small appliances, as well as laboratories.

prevents improper insertion of foreign objects. Meets 2017 National Electrical Code® Tamper-Resistant requirements.

Multiple colors and finishes. Painted finishes of black, gray, ivory, and white, as well as anodized aluminum and stainless steel versions integrate easily with any room decor.

Specifications

| General Info | | | |
|-----------------------|---|--------------------|------------------------|
| Product Line | Wiremold | Color | Silver |
| UPC Number | 786776188066 | Country Of Origin | United States |
| Number of Receptacles | 5 | Application Sector | Residential/Commercial |
| Standard | cULus Listed Multioutlet Assembly: File E15191 Guide PVGT/PVGT7 | Туре | Plugmold |
| Dimensions | | | |
| Product Width US | 36.0 in | Product Weight US | 1.79 lb |
| Product Volume US | 44.01 cu in | Product Depth US | 0.75 in |
| Product Height US | 1.63 in | | |

| Listing Agencies / 3rd Party Agencies | | | | | |
|---------------------------------------|-----------------|-------------------------------|---------|--|--|
| cULus ListingNumber | E15191 | cULus Listed | Yes | | |
| Buy American Act Compliance | | | | | |
| NAFTA | Yes | | | | |
| Additional Information | | | | | |
| RoHS Conformant | Yes | Product Environmental Profile | Yes | | |
| Technical Information | | | | | |
| Frequency Rating | 60 Hz | Amperage | 15 A | | |
| Enclosure Type | Stainless Steel | Voltage | 125.0 V | | |
| | | | | | |